

hearing protectors

- "Anti-Noise" Protectors
- Rugged, Comfortable & Lightweight
- Effectively Seal the EarMinimum Pressure
- Permits Conversational Speech &
- Warning Signals

 Meets All Requirements of Occupational Safety & Health Act



SAFETY EQUIPMENT

kleen air masks

*#*506 Box of 25


(Replacement Filters)

- Protects Against Non-Toxic Dusts, Mists & Paint Sprays
- Pliable Lightweight Frame Molds to **Facial Contours**



ear plug

Molded of soft elastometric plastic. Lightweight, non-irritating. Offer effective attenuation, permit hearing at normal conversational levels. Insert, turn tab to back. Resistant to ear wax and soil. Will not deteriorate or harden. Washable. One pair per plastic carrying case.




safety caps

Complies with OSHA Requirements... N.Y. State B.S.A. approval No. 7566/Wash., D.C. approval No. D.C.I.S...571-1

- New, improved TUF-E head protection injection molded with high density polyethylene.

 • Penetration, impact, chemical and voltage resistant.
- Popular rain trough design prevents water from running dow neck.
- 4-point or 6-point suspension, with built-in nape strap. Fully adjustable for head sizes 6-1/2 to 8.
- Weighs only 11-1/2 ozs. each, packed 20 per carton.



- Soft Vinyl Frame
- Perforations for Maximum Ventilation
- Optical Quality Distrotion Free
- · Clear Body & Lense · Splash Proof

FLASHLIGHTS


SAFETY LIGHTS

SLIP-ON WAND LIGHT



SELF-STORING WAND

(Batteries Not Included)



- handy FLASHLIGHT!
- Uses as a GUIDE LIGHT for parking aircraft, etc. during periods of low visibility!
- Self-storing wand.
- No pilot should be without this light! **#548**



extension light

Portable flourescent, OSHA approved 15 watts, 110 volts. Safe, rugged, burns cool, cord-reach 20 feet. Heavy duty. Comes with on/off switch.

#29 . .

220V Available

midget light

6 watt 14 ft. coiled cord. 12" OAL

#6cc

Heavy Duty Lights for HAZARDOUS LOCATIONS

The Hazardous Locations Fluorescent Work Light represents the ultimate in safety and dependability for work in high-hazard areas.

Designed to aircraft specifications.


•All aluminum body, with special compounded bumper guards & end caps, protects against damage from falling objects, bumping or dropping.

•Enclosed ballast, remote from light, to keep heat from work area. All ballasts are high voltage

tested to a minimum of 1500 volts, from coils to frame & coil to coil. (Isolated Ballast Available.) Plug: Explosion proof plug is required. The hazardous (classified) location ratings of an attachment plug may be more restrictive than those of the light assembly. In such cases the ratings of the attachment plug take precedence. If light is to be hard wired, an explosion proof wall fixture must be used. Furnished without plug.

220V, 50 HZ **ALSO AVAILABLE**

EP300 SERIES



EP300 SERIES WITH ISOLATED BALLAST

CATALOG NUMBER	WATTS	CORD LENGTH	OVERALL DIAMETER	OVERALL LENGTH
EP300-013-025-IB	13	25'	3-1/2"	14-3/4"
EP300-013-050-IB	13	50'	3-1/2"	14-3/4"

